



Date

Name

Client

Project name

Quote#


Type/Quantity

Specification Sheet

GRAND DIRO TRIMLESS D 111

202 15 61 00

[Weblink](#)



Cutout shape/size:  Ø KIT mm

Recessed depth: 150 mm

ADJUSTABLE 0°- 20° / 360°

G53 // 12V // EXCL. TRANSFO

 1 x QR-LP111 max.100W

Class: III

Weight: 0.3 KG

Protection level: IP20

Minimum distance: 1,0m

Options: TRANSFO


Requirements: MOUNTING KIT R143 TRIMLESS

For detailed installation instructions, please consult the manual. [202_15_61_00_HAND.pdf](#)

22/05/2019 23:38:52

GRAND DIRO TRIMLESS D 111
202 15 61 00


Ceiling compatibility



System ceiling

Only with


MOUNTING KIT R143 TRIMLESS



Plasterboard

Only with


MOUNTING KIT R143 TRIMLESS



Stucanet

Only with


MOUNTING KIT R143 TRIMLESS



Concrete + plaster

Only with


MOUNTING KIT R143 TRIMLESS



Lintel + plaster

Only with

MOUNTING KIT R143 TRIMLESS



Hollow-core slab + plaster

Only with


MOUNTING KIT R143 TRIMLESS

GRAND DIRO TRIMLESS D 111
202 15 61 00

Related references


CONTROL GEAR, BALLAST AND TRANSFORMERS

[Weblink / Specs sheet](#)



TRANSFO 100W
200 46 10
220-240V / 50-60Hz

[Weblink / Specs sheet](#)



TRANSFO 50W
200 46 06
220-240V / 50-60Hz

GRAND DIRO TRIMLESS D 111
202 15 61 00

Related project picture of product family:

